



Be ahead



# DEIMOS BT A





## Sliding gate automation systems



d-track





er ready



ee link



24 V



Range of operators for sliding gates weighing up to 600 Kg.  
Maximum leaf speed up to 16 m/min.  
Residential use.  
Power supply 24V.





## Sliding gate automation systems

### DEIMOS BT A

Code	Name	Description
P925222 00002	DEIMOS BT A400	Operator 24 V for sliding gates up to 400 kg in weight. Leaf speed 12 m/min. Limit switch Electromechanical
P925222 00003	DEIMOS BT A400 V	Operator 24 V for sliding gates up to 300 kg in weight. Leaf speed 16 m/min. Limit switch Electromechanical
P925222 00005	DEIMOS BT A400 SQ	Operator 24 V for sliding gates up to 400 kg in weight. Leaf speed 12 m/min. Limit switch Electromechanical
P925222 00006	DEIMOS BT A400 V SQ	Operator 24 V for sliding gates up to 300 kg in weight. Leaf speed 16 m/min. Limit switch Electromechanical
P925222 00001	DEIMOS BT A400 120	Operator 120 V for sliding gates up to 400 kg in weight. Leaf speed 12 m/min. Limit switch Electromechanical
P925222 00004	DEIMOS BT A400 V 120	Operator 120 V for sliding gates up to 300 kg in weight. Leaf speed 16 m/min. Limit switch Electromechanical
P925224 00002	DEIMOS BT A600	Operator 24 V for sliding gates up to 600 kg in weight. Leaf speed 12 m/min. Limit switch Electromechanical
P925224 00003	DEIMOS BT A600 V	Operator 24 V for sliding gates up to 360 kg in weight. Leaf speed 16 m/min. Limit switch Electromechanical
P925224 00005	DEIMOS BT A600 SQ	Operator 24 V for sliding gates up to 600 kg in weight. Leaf speed 12 m/min. Limit switch Electromechanical
P925224 00006	DEIMOS BT A600 V SQ	Operator 24 V for sliding gates up to 360 kg in weight. Leaf speed 16 m/min. Limit switch Electromechanical
P925224 00001	DEIMOS BT A600 120	Operator 120 V for sliding gates up to 600 kg in weight. Leaf speed 12 m/min. Limit switch Electromechanical
P925224 00004	DEIMOS BT A600 V 120	Operator 120 V for sliding gates up to 360 kg in weight. Leaf speed 16 m/min. Limit switch Electromechanical
R925267 00002	DEIMOS BT KIT A400 FRA	Complete kit 24 V for sliding gates weighing up to 400 kg. Leaf speed 12 m/min. Limit switch Electromechanical
R925271 00002	DEIMOS BT KIT A600 FRA	Complete kit 24 V for sliding gates weighing up to 600 kg. Leaf speed 12 m/min. Limit switch Electromechanical

#### HAMAL: Control panel with trimmer and dip switch for one operator, 230V - 70W

##### HAMAL - Built in



- Control panel with trimmer and dip switch for one operator, 230V - 70W
- Application: built-in control unit for one 24V operator for sliding gates
- Card power supply: 230 V single-phase
- Operator power supply: 24V 80W
- Main features: removable terminal blocks with new standard colour-coding, dip-switch programming and potentiometers, incorporated dual channel receiver, D-Track anti-crushing system, slowdown during opening and closing
- Principal functions: automatic closing, pedestrian opening with remote control only, 8k2 obstruction sensor input, rapid closure

	DEIMOS BT A400	DEIMOS BT A400 V	DEIMOS BT A400 SQ	DEIMOS BT A400 V SQ	DEIMOS BT A400 120	DEIMOS BT A400 V 120
Control unit	HAMAL	HAMAL	---	---	HAMAL	HAMAL
Board power supply	230 V	230 V	230 V	230 V	120 V	120 V
Supply voltage	24 V	24 V	24 V	24 V	120 V	120 V
Power consumption	50 W	50 W	50 W	50 W	50 W	50 W
Max. door/gate weight	400 kg	300 kg	400 kg	300 kg	400 kg	300 kg
Gate speed	12 m/min	16 m/min	12 m/min	16 m/min	12 m/min	16 m/min
Type of limit switch	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical
Pinion module	4	4	4	4	4	4









## Sliding gate automation systems

	DEIMOS BT A400	DEIMOS BT A400 V	DEIMOS BT A400 SQ	DEIMOS BT A400 V SQ	DEIMOS BT A400 120	DEIMOS BT A400 V 120
Slowdown	Yes	Yes	Yes	Yes	Yes	Yes
Locking	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Release	Lever-operated with personal key	Lever-operated with personal key	Lever-operated with personal key	Lever-operated with personal key	Lever-operated with personal key	Lever-operated with personal key
Impact reaction	D-Track	D-Track	D-Track	D-Track	D-Track	D-Track
Frequency of use	intensive	intensive	intensive	intensive	intensive	intensive
Protection rating	IP24	IP24	IP24	IP24	IP24	IP24
Environmental conditions	-20 ÷ 55 °C	-20 ÷ 55 °C	-20 ÷ 55 °C	-20 ÷ 55 °C	-20 ÷ 55 °C	-20 ÷ 55 °C

	DEIMOS BT A600	DEIMOS BT A600 V	DEIMOS BT A600 SQ	DEIMOS BT A600 V SQ	DEIMOS BT A600 120	DEIMOS BT A600 V 120
Control unit	HAMAL	HAMAL	---	---	HAMAL	HAMAL
Board power supply	230 V	230 V	230 V	230 V	120 V	120 V
Supply voltage	24 V	24 V	24 V	24 V	120 V	120 V
Power consumption	70 W	70 W	70 W	70 W	70 W	70 W
Max. door/gate weight	600 kg	360 kg	600 kg	360 kg	600 kg	360 kg
Gate speed	12 m/min	16 m/min	12 m/min	16 m/min	12 m/min	16 m/min
Type of limit switch	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical	Electromechanical
Pinion module	4	4	4	4	4	4
Slowdown	Yes	Yes	Yes	Yes	Yes	Yes
Locking	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical	Mechanical
Release	Lever-operated with personal key	Lever-operated with personal key	Lever-operated with personal key	Lever-operated with personal key	Lever-operated with personal key	Lever-operated with personal key
Impact reaction	D-Track	D-Track	D-Track	D-Track	D-Track	D-Track
Frequency of use	intensive	intensive	intensive	intensive	intensive	intensive
Protection rating	IP24	IP24	IP24	IP24	IP24	IP24
Environmental conditions	-20 ÷ 55 °C	-20 ÷ 55 °C	-20 ÷ 55 °C	-20 ÷ 55 °C	-20 ÷ 55 °C	-20 ÷ 55 °C

## RECOMMENDED ACCESSORIES

	<b>new</b> D114093 00003 - <b>RADIUS LED BT A R1</b> Flashing light with incorporated antenna for motors with power supply 24 V.		<b>new</b> D114168 00003 - <b>RADIUS LED BT A R1 W</b> Flashing light with built-in antenna for motors with a 24 V power supply. White flashing light.
	<b>new</b> D114094 00003 - <b>RADIUS LED BT A R0</b> Flashing light without incorporated antenna for motors with power supply 24 V.		<b>new</b> P111782 - <b>COMPACTA A20-180</b> Pair of photocells adjustable 180 ° horizontally. Range 20m. Power supply 12 – 33Vac / 15 – 35Vdc
	D221073 - <b>CP</b> plastic rack, 4-module, cross-section 22 x 22 mm, length 1 m, screw-fitted into slots Max. load capacity 600 kg.		D571053 - <b>CVZ</b> steel rack, 4-module, cross-section 30 x 12 mm, length 1 m, screw on supports Max. load capacity 1000 kg.





## Sliding gate automation systems

### RECOMMENDED ACCESSORIES

	N999320 - <b>CVZ-S</b> steel rack, 4-module, cross-section 30 x 8 mm, length 1 m, screw-fitted on supports Max. load capacity 800 kg.		N999151 - <b>SFD</b> Base plate for DEIMOS series (supplied with operator)		
	P125035 - <b>SL BAT2</b> Emergency battery kit for Deimos BT A, Ares BT A, Deimos Ultra BT A, Ares Ultra BT A.				





## Sliding gate automation systems

# What is U-Link?

The technology that gives you more power

U-Link, Universal Link, is an exclusive BFT platform that can be used to create high-tech ecosystems. In Home Access Automation, it can be used to communicate with all home access automation devices of any brand. This saves you time and allows you to control everything easily and without any worries.

### It is intuitive

Easy to install and to use

### It is scalable

You can add as many devices as you want

### It is flexible

It allows you to create groups of interconnected products

### It is practical

Works with or without an internet connection

### It is functional

Its settings can be controlled remotely using dedicated applications



## Sliding gate automation systems

### Everything on one screen: find out more about this amazing technology

A world-exclusive platform that **can be used to create high-tech ecosystems** offering a vast range of solutions for many different sectors.

This proprietary platform which is a key feature of BFT products, thanks to the B-EBA cards and the Clonix U-Link receiver, is suitable for any protocol or product for access automation (including BFT products non-BFT ones and older versions) and it can be used in a variety of different sectors. This means any device becomes a smart device which can be interconnected with other systems, using a language that is becoming universal.




#### U-Control HOME

U-Control HOME is the application that allows you to open the gate to your home and to remotely control BFT automations using your own smartphone. The iOS version can be used to automatically open the automation when you are close to it.



#### U-Base 2

A software package for installation, performing maintenance and identifying any faults in the U-Link compatible operators, easily and conveniently.



#### U-SDK

U-SDK is the application which allows BFT automations to be made compatible and easily integrated with a BMS network.



#### Clonix U-Link

Connect non-native U-Link and non-BFT products to U-Link systems.

Is it possible to connect non-native U-Link BFT operators or other brands of products to U-Link? Yes, thanks to the Clonix receivers. Accessories which accept no limits.



#### B-EBA

A direct link to your operators.

The B-EBA expansion cards make it possible to connect external devices such as PCs, smartphones and tablets to a BFT operator and a Clonix receiver or to connect multiple BFT products in a U-Link network. These accessories integrate with U-Link technology and with Bluetooth, Wifi, Z-Wave and TCP/IP protocols as well as with the RS485 serial interface. A device that demonstrates exactly what BFT means by interconnectivity.

